



www.ORingnet.com

ORing Company Profile IIOT

Get connected Anytime, Anywhere.

公司簡介-主要里程碑



Weidmüller 

2019

德國Weidmüller集團入股ORing。
獲得10萬台IoT設備訂單，取得桃園市智慧路燈案標案。

2018

NB-IOT / CAT-M1產品發表，威力工業物聯網產品大規模部署

2017

IIOT/I/O-Gateway-ORIO以及連結傳感偵測器通過了由諾基亞/愛立信實驗室進行的NB-IoT測試，
並推出ORing的第一個ORing Pass雲端平台

2016

推出第一個配備銅線介面與PoE功能的軌道車廂用2.5G/10G乙太網路交換器

2015

威力工業網絡公司通過了國際鐵路行業標準認證
發表通過IEC-61850認證三層且具10G速度傳輸的模組化交換機
發表通過IEC-61850導軌式交換機

2014

提升X-Roaming轉換速度至60ms / 發表為海洋應用設計具IEC 60945認證產品

2013

通過UL C1D2防爆認證 / 整合媒體複聯通訊協定(MRP)與Modbus至交換機產品中

2012

發表專為電廠設計具IEC-61850認證的交換機 /
序列設備伺服器支援Windows 7 & Windows 8

2011


發表專為軌道運輸設計具EN50155的系列產品/AXIS通訊聯手開發IP監視器市場

2010

發表工規全Giga傳輸速度的網路交換機
發表大功率支援IEEE 802.3at乙太網供電全Giga交換機

ORing Worldwide

- 2005 年成立
- 資本額 500,000,000
- 實收資本額 153,036,000
- 總部及代工廠位於新北市。
- 全球員工 > 200 人 ; R&D > 130 人
- 4 間海外分公司 (China, Europe , USA, India)
- 全球技術支援及代理商
- 5 年設備保固



產品介紹及應用分析-八大產品線



ORing Product Line



Industrial Ethernet Switch

- Managed L2/L3
- Lite-managed
- Unmanaged
- Copper/Fiber
- 10/100/1000Mbps and 10G
- Fixed or Modular design
- PoE 802.3af/at/bt
- PoE Injectors/Splitters/Extenders

Industrial Media Converter

- Copper/ PoE to Optical Fiber
- Ethernet to VDSL

Industrial Serial Products

- Serial to Ethernet/Wireless Device Server
- Serial to Optical Fiber
- Serial to Serial / Repeater
- Modbus TCP to Modbus RTU


Wireless Access Point

- Industrial Wireless Access Point
- Outdoor IP67 Wireless Access Point
- IEEE 802.11a/b/g/n/ac
- Dual RF

Industrial VPN Router

- Industrial Cellular VPN Router
- Outdoor IP67 Cellular VPN Router
- 3G and 4G LTE
- Dual Modem / Dual SIM
- IEEE 802.11 a/b/g/n


ORing IoT Product Line. (MQTT-Sparkplug compliance)



ORing + Ignition solutions

From edge to the cloud , From smart factory to smart City

- ORing sensor node devices and IOT gateway are MQTT-Sparkplug compliance
- ORing Ignition Edge gateway is ignition on board and support docker programming for edge computing
- ORing IOT platform (ORing-PaaS) with MQTT-Sparkplug broker and ignition connector





www.ORingnet.com

ORing IIoT 介紹

Dao Chen

Get connected Anytime, Anywhere.

物聯網引言

1

1. 既有經驗
2. 物聯網常見技術

物聯網商機及成功案例

2

1. 智慧交通
2. 智慧防汎
3. 消防聯網
4. 地層下陷預防
5. 共享停車
6. 智慧城市-智慧路燈

ORing 產品介紹

3

1. 平台及硬體架構
2. 產品說明
3. 節電設計說明
4. 緊急APP 及平台
5. Open Gateway

Why ORing?

4


1. 物聯網成功關鍵

ORing

Top1 IIoT聯網設備廠商，NB-IoT 設備累計出貨 > 120,000pcs

專案名稱	年度
桃園市水銀路燈汰換統包工程（南區）	2016
亞洲矽谷IoT 場域	2017
107年度臺北科學藝術園區智慧型路燈設置統包工程服務	2018
107年度延平南路等處LED智慧路燈統包工程	2018
泰山區107年度試辦智慧路燈提升效率	2018
高速公路智能調控LED路燈試辦工程	2018
國家研究院，沙崙能源環境智慧管理平台 研發與展示案	2018
高雄市哈瑪星社區智慧路燈示範計畫	2018
牡丹水庫智慧營運與管理技術建置第二期	2018
臺南市智慧防汛網第一期建置計畫	2018
108年度二河局轄區洪水預警及防汛整合作業	2018
水湳智慧城智慧路燈系統前瞻建置計畫統包工程	2019
台中水湳智慧城防汙工程	2019
南寮漁港智慧燈控	2019
桃園市全面換裝智慧路燈既維護案	2019
高雄市全面換裝智慧路燈既維護案	2020
水利署深耕培力計畫	2020
消防主機聯網	2020
Uspace 共享停車	2020

「互通互聯」的發展歷程



- 成本低
 - 傳輸距離遠
 - 穿透性佳
 - 電量低，不須佈線
 - 易設定，快速整合
 - 資料庫技術提升

MOT 常見技術

- 傳輸距離遠
- 穿透性高
- 價格低
- 耗電量低

標準LPWAN技術

- 傳輸條件嚴苛，訊號涵蓋未完全

- 電池壽命即為產品壽命，越省電，壽命越長

- 衆多應用，眾多平台，不同資料格式轉換

- 巨量設備建置，設定，管理

物聯網技術需求

- ORIO
多備援的傳輸技術
- 低功耗的MCU使用
- 針對產品特性設計節電腳本

- Open Gateway

- Magi-Collect

- Magi-Connect

- Magi-City
Management System

威力核心技術

物聯網引言

1

1. 既有經驗
2. 物聯網常見技術

物聯網商機及成功案例

2

1. 智慧交通
2. 智慧防汛
3. 消防聯網
4. 地層下陷預防
5. 共享停車
6. 智慧城市-智慧路燈

ORing 產品介紹

3

1. 平台及硬體架構
2. 產品說明
3. 節電設計說明
4. 緊急APP 及平台
5. Open Gateway

Why ORing?

4

1. 物聯網成功關鍵


物聯網商機開發來源




社會需求，民氣可用
交通安全
智慧防汛
消防聯網



政府需求，循循善誘
地層下陷問題改善



新商業模式
Uspace 共享停車



智慧管理，ROI 回本
智慧路燈管理

五楊霧氣警示燈控制器 - 發現需求

起霧颳風路漆黑 駕駛開「五楊」心驚

記者 林志偉 林君航 桃園 報導 ① 2013/02/25 17:09

小 中 大

部分通車的五楊高架橋，卻讓駕駛晚上開得心驚驚，有民眾日前行經中壢路段，不但沒有路燈，而且當晚還起霧、颳大風，前方一片漆黑，能見度頂多50公尺，讓駕駛膽戰心驚，而國工局表示，未來將會在部分路段加設霧中行車警示器，讓駕駛沿著護欄小心行駛。

駕駛：「超恐怖的耶。」


前方一片漆黑，不但沒有路燈，更慘的是竟然還起大霧、颳大風，駕駛嚇得小心行駛，就怕一閃神發生車禍意外。駕駛：「什麼都看不到。」

- 傳輸條件嚴苛，且基地台涵蓋未完全
- 拉電困難，電池或太陽能系統決定系統壽命



五楊霧氣警示燈控制器 - 技術說明

- 本地端智慧調控
(起霧才開燈)
- 太陽能充放電控制系統
(確保系統效率)
- 電池健康度警報及用電資料
(平台管理)



台南防汛系統-發現需求



台南永康社區淹水！住戶忙清掃南市議員忙打口水戰
udn 聯合新聞網 - 20 小時前

50多年來從未淹水的永康區中華路154巷淹水，今天趁天晴住戶忙著清理 ... 台南市政
府表示，目前已調派四部抽水機待命，只要下雨就啟動抽水， ...

台南永康雨下30毫米竟淹水 疑箱涵遭灌漿阻塞
Yahoo奇摩新聞 (新聞發布) - 17 小時前

台南永康淹水24小時清淤預計明晚完成
台灣大紀元 - 1 分鐘前

台南永康雨下20分鐘...竟離奇淹水！王定宇控：人為因素
三立新聞網 (新聞發布) - 2018年9月8日

台南》永康中華路淹出民怨代理市長李孟諺親自進箱涵
中時電子報 (新聞發布) - 17 小時前

疑地下箱涵阻塞台南永康水淹及膝
評論 - 華視新聞 - 2018年9月8日



Yahoo奇摩 ...



台灣大紀元



華視新聞



三立新聞網 ...



中時電子報 ...



自由時報電 ...


- 傳輸條件嚴苛，且基地台涵蓋未完全
- 拉電困難，電池或太陽能系統決定系統壽命
- 需整合眾多設備及系統

台南防汛系統-技術說明

- LoRaWAN + NB-IoT 雙備援系統
- 跨通訊技術傳輸平台管理
- 多設備整合 (Open Gateway)

雨量計
風向計
水位計
流量計
油量計
電壓計

GPS
馬達控制
閘門控制




Solar Charger Control / Sensor Gateway / RF Redundant / Water Proof






暴雨結果大不同





台南防汛系統-傳輸架構技術說明



智慧消防- 發現需求

4月26日，台北林森錢櫃大火奪走6條人命，更燒出公安問題。為了避免又有業者便宜行事，關掉火警受信繩機，阻礙黃金逃生時間，台北市消防局今（2）天到了另外一家星聚點KTV，舉辦消防搶救演練，模擬火警發生的疏散SOP，要是消防設備被關掉，都會第一時間通報，而錢櫃也派各分店的「防火管理人」前來觀摩。


警鈴聲大作，KTV的B1廚房竄出濃煙、火舌，打火班先行出動。店員第一時間，趕緊拿滅火器搶救，疏散包廂民眾，甚至拉水線自救。

只是火煙實在太大，消防隊獲報也趕到，深入火場滅火，外頭雲梯車緩緩升空，救出受困民眾。台北市星聚點KTV，全員出動，包含警消一共動員150人，逼真演練。



- 八大行業仍為了抽菸，施工等需求，偷關受信設備
- 政府只能透過臨檢巡查，但通常臨檢前，業主已經重啟系統，永遠稽查不到問題

智慧消防- 系統架構



既有消防系統，採用外掛
Sensor，偵測廣播設備電力，消
防主機的乾接點，確認是否有被
偷關



新型態受信主機，具有Modbus
介面可直接透過ORing 設備聯網

智慧消防- 平台畫面

高雄市政府
Kaohsiung City Government

2020/10/24 15:21

4F平面圖

連線率
94.2%
4146/4563

告警資訊

- 消防設備01 主機電源斷電
- 消防設備02 廣播電源電流過低
- 消防設備03 警報器電流過低
- 消防設備04 主機備援電壓過高
- 消防設備05 設備離線
- 消防設備06 RSSI 數值偏小
- 消防設備07 主機電源斷電
- 消防設備08 廣播電源電流過低
- 消防設備09 警報器電流過低
- 消防設備10 主機備援電壓過高
- 消防設備11 設備離線
- 消防設備12 RSSI 數值偏小

地區告警統計


告警類別統計

設備導入趨勢圖

物聯網商機開發來源




社會需求，民氣可用
交通安全
智慧防汛
消防聯網



新商業模式
Uspace 共享停車




政府需求，循循善誘
地層下陷問題改善



智慧管理，ROI 回本
智慧路燈管理

智慧培力-發現需求



- 地層下陷嚴重
- 地下水超抽
- 農民不聽勸導

智慧培力-問題解決

Step 1 : 提供農民遠端控制功能，不需要巡田水

Step 2 : 預約抽水時間改為預約抽水量

Step 3 : 依據農民預約狀況及地下水觀測井的數據，
調整各田地抽水時間，錯開抽水尖峰時段

Step 4 : 農民走向智慧農業，藉由平台管理



Map-device-schedule 15d




Map-device-schedule-delete 15d

智慧培力-技術架構


Open Gateway 系統架構

- 整合水流計，馬達用電
- 整合各式控制IO
- 影像監控



Smart IO 功能

- 馬達空轉，水位過低，抽不到水
- 未抽水，但水壓過高，仍出水
- 馬達開啟，電流異常



物聯網商機開發來源




社會需求，民氣可用
交通安全
智慧防汛
消防聯網



政府需求，循循善誘
地層下陷問題改善



新商業模式
Uspace 共享停車




智慧管理，ROI 回本
智慧路燈管理

智慧停車 - 既有產品比較



USPACE智慧地鎖



傳統手動地鎖



鐵柵欄

操控性	全自動遙控升降	需下車手動操控不易	需搬動，容易吹倒
阻擋性	侵入警報，自動回彈	未上鎖容易搬動	疑被移動，阻擋性差
耐壓性	塑鋼纖維，5公噸耐壓	輒壓即損，損壞率高	面積單薄易損壞
防水性	IP6X防水、防鏽處理	易脫漆、生鏽生雜草	易脫漆、生鏽


智慧停車 – 社區收益比較

案例
明園大廈



\$56,000

每月增加管委會營收




智慧停車 – 個人收益比較

案例 住家車位



\$4,500

每月車位閒置臨停營收



物聯網商機開發來源



社會需求，民氣可用
交通安全
智慧防汛
消防聯網



政府需求，循循善誘
地層下陷問題改善



新商業模式
Uspace 共享停車



智慧管理，ROI 回本
智慧路燈管理

桃園智慧路燈 PFI 專案

Present Three Awards of 2019 Smart City / Mayor Cheng: keep developing smart city and improving the administrative efficiency

Release Unit : Department of Public Information

Release Date : 2019-04-10

Providers : Press Liaison Section



Taoyuan City Mayor Cheng Wen-Tsan hosted the municipal administrative meeting on April 10 and accepted "2019 Smart City Awards" won by Department of Youth Affairs, Department of Information Technology, Department of Water Resources, and Department of Public Works. Mayor Cheng stated "2019 Smart City Summit & Expo" was held at Taipei Nangang Exhibition Center from March 26 to 29 this year (2019). It was the largest professional expo of smart city, covering smart medicine, smart architecture, smart education, smart energy, smart transportation, and smart security protection. Taoyuan City's Department of Youth Affairs and Department of Information Technology won the first prize of "2019 The Best Start-Up Friendly City" among municipalities; Department of Water Resources won "2019 Smart City Innovative Application Award" with the smart underground water management system; Department of Public Works won "2019 Smart City Innovative Application Award" with the smart street lights and the IoT application platform. These three awards showed Taoyuan's broad application of smart city development.

數量

160k pcs

預算

56 億 (小於既有路燈電費及每年維護費)

合約內容

- 新設智慧路燈
- 維運8 and 17年

KPI

- 維修效率 < 24hr
- 偵測準確度 > 99.7 %
- 路燈故障數量
- 居民回饋或縣市承辦評分
- 節能績效


節電費用

60%

Before : 250W HPS

After : 100W LED



桃園智慧路燈系統架構



桃園智慧路燈平台畫面




- Group Management
 - Alarm Notice
 - Street Light Information



桃園智慧路燈工程管理

The screenshot shows the 'Maintenance Task Management' section of the system. It lists 12 tasks with columns for task ID, location, status, and creation date. A search bar and export CSV button are at the top.

任务ID	位置	状态	创建时间
N20200101178	071004 桃園	待施工	2020/01/21 17:55:47
N20200101177	待申請	待施工	2020/01/21 15:58:52
N20200101167	待申請	待施工	2020/01/21 17:02:46
N20200101165	待申請	待施工	2020/01/21 15:58:53
N20200101163	待申請	待施工	2020/01/21 15:58:52
N20200101162	待申請	待施工	2020/01/21 15:58:53
N20200101161	待申請	待施工	2020/01/21 15:58:57
N20200101160	071004 桃園	待申請	2020/01/21 14:42:40
N20200101159	071004 桃園	待申請	2020/01/21 18:01:14



The screenshot shows a detailed view of a task with fields for location, status, and creation date. Below the form is a grid of images showing streetlights.

位置	狀態	創建時間
071004 桃園	待施工	2020/01/21 17:55:47

桃園線上即時資訊

	北	蘆竹區	大園區	新屋區	中壢區	平鎮區	觀音區
		點數	正常	警戒	待修	已修	總數
正京	蘆竹區	11,589	13,125	10,177	23,172	11,244	13,691
	大園區	11,589	13,125	10,177	23,172	11,244	13,691
	新屋區	0	0	0	0	0	0
裕修	蘆竹區	0	0	0	0	0	0
	大園區	0	0	0	0	0	0
	新屋區	0	0	0	0	0	0
南	桃園區	17,458	14,588	11,370	10,675	14,882	1,910
	龜山區	17,458	14,588	11,370	10,675	14,882	1,910
	八德區	0	0	0	0	0	0
觀音	大溪區	0	0	0	0	0	0
	楊梅區	0	0	0	0	0	0
	復興區	0	0	0	0	0	0
觀音	觀音區	0	0	0	0	0	0
	總數	0	0	0	0	0	0
	正常	0	0	0	0	0	0

桃園智慧路燈庫存管理

- Every controllers should provide the IMEI and IMSI number to get the approval letter before the installation. And get the system ID and Key to do the security control.
- Monitor the stock quantity to keep the safety volume.

The screenshot displays two instances of the "Controller Serial Number Search" interface from the "Tainan Intelligent Streetlight Inventory Management System".

Left Interface: Shows a search form with fields for Production Date (起) and Production Date (迄), and a dropdown for Production Quantity. The results table lists five entries:

序號	生產日期	筆數	換裝數	通過日期	廠商	功能
1	2019/09/24	2,960	2,854	2019/09/26	南區	顯示資料
2	2019/10/01	6,000	5,101	2019/10/23	南區	顯示資料
3	2019/11/01	11,350	6,772	2019/12/28	南區	顯示資料
5	2019/12/24	9,000	5,618	2019/12/28	南區	顯示資料

Right Interface: Shows a search form with a dropdown for Status (狀態) set to "全部" (All). The results table lists 75 entries, each with a checkmark and a detailed link. The columns include Controller ID, Status, Model, Type, Production ID, Production Date, Transmission Method, IMEI, and IMSI.

序號	已使用	控制器編號	廠牌	型號	生產批號	生產日期	傳輸方式	IMEI	IMSI
61	<input checked="" type="checkbox"/>	LC02_OR000000019087A05453	ORing	OL-N2T5GPA1-NBG-UR	019087A05453	2019/09/24	NB-IoT	356726109376749	466978
62	<input checked="" type="checkbox"/>	LC02_OR000000019087A05454	ORing	OL-N2T5GPA1-NBG-UR	019087A05454	2019/09/24	NB-IoT	356726109376840	466978
63	<input checked="" type="checkbox"/>	LC02_OR000000019087A05455	ORing	OL-N2T5GPA1-NBG-UR	019087A05455	2019/09/24	NB-IoT	356726109376822	466978
64	<input checked="" type="checkbox"/>	LC02_OR000000019087A05456	ORing	OL-N2T5GPA1-NBG-UR	019087A05456	2019/09/24	NB-IoT	356726109372373	466978
65	<input checked="" type="checkbox"/>	LC02_OR000000019087A05457	ORing	OL-N2T5GPA1-NBG-UR	019087A05457	2019/09/24	NB-IoT	356726109361568	466978
66	<input checked="" type="checkbox"/>	LC02_OR000000019087A05459	ORing	OL-N2T5GPA1-NBG-UR	019087A05459	2019/09/24	NB-IoT	356726109372367	466978
67	<input checked="" type="checkbox"/>	LC02_OR000000019087A05461	ORing	OL-N2T5GPA1-NBG-UR	019087A05461	2019/09/24	NB-IoT	356726109361535	466978
68	<input checked="" type="checkbox"/>	LC02_OR000000019087A05464	ORing	OL-N2T5GPA1-NBG-UR	019087A05464	2019/09/24	NB-IoT	356726109361592	466978
69	<input checked="" type="checkbox"/>	LC02_OR000000019087A05465	ORing	OL-N2T5GPA1-NBG-UR	019087A05465	2019/09/24	NB-IoT	356726109376568	466978
70	<input checked="" type="checkbox"/>	LC02_OR000000019087A05466	ORing	OL-N2T5GPA1-NBG-UR	019087A05466	2019/09/24	NB-IoT	356726109361451	466978
71	<input checked="" type="checkbox"/>	LC02_OR000000019087A05467	ORing	OL-N2T5GPA1-NBG-UR	019087A05467	2019/09/24	NB-IoT	356726109361469	466978
72	<input checked="" type="checkbox"/>	LC02_OR000000019087A05469	ORing	OL-N2T5GPA1-NBG-UR	019087A05469	2019/09/24	NB-IoT	356726109361519	466978
73	<input checked="" type="checkbox"/>	LC02_OR000000019087A05470	ORing	OL-N2T5GPA1-NBG-UR	019087A05470	2019/09/24	NB-IoT	356726109361444	466978
74	<input checked="" type="checkbox"/>	LC02_OR000000019087A05473	ORing	OL-N2T5GPA1-NBG-UR	019087A05473	2019/09/24	NB-IoT	356726109393975	466978
75	<input checked="" type="checkbox"/>	LC02_OR000000019087A05474	ORing	OL-N2T5GPA1-NBG-UR	019087A05474	2019/09/24	NB-IoT	356726109393974	466978

桃園智慧路燈KPI管理



PS5.1契約工作達成落實度與滿意度 契約工作達成落實度與滿意度

當期指標評分總表 當期指標評分總表

南區	北區	評核時期(期間)	評核期間	指標類型(類型占分)	類型得分	績效指標(指標占分)	指標得分
PS1		1	2019/07/12~2020/07/11	節能路燈換裝完成度指標 (25)	22.50	PS1.1 初期換裝完成率 (25)	22.50
				PS2.1 光色品質 (2.5)	1.17	PS2.2 光強度控制 (2.5)	1.58
				PS2.3 平均照度 (4.5)	2.25	PS2.4 照度品質 (2.5)	1.09
PS2		11.72	2019/07/12~2020/07/11	節能服務合宜性指標 (20)	11.72	PS2.5 發光效率 (2)	0.57
				PS2.6 當作物光害防制落實度 (3)	2.20	PS2.7 規範性 (3)	2.85
PS3		23.70	2019/07/12~2020/07/11	節能服務持續性指標 (25)	23.70	PS3.1 有效照明維持率 (12)	12.00
				PS3.2 平日修復效率 (6.5)	6.50	PS3.3 後續維修效率 (6.5)	5.20
				PS4.1 智能路燈系統維護率 (10)	0.00	PS4.2 系統登錄詳實度 (5)	0.00
PS4		9.44	2019/07/12~2020/07/11	智能路燈管理系統操作順暢度指標 (50)	9.44	PS4.3 智能路燈回應時間 (5)	5.00
				PS4.4 智能路燈異常訊息回應正確性 (5)	4.44	PS4.5 系統可靠度 (25)	0.00
				PS5.1 契約工作達成落實度與滿意度 (5)	4.14	PS5.1 契約工作達成落實度與滿意度 (5)	4.14
				總分(125)	71.50		

KPI System will record the period.
If > 24hrs. System will penalty the bidder.

Auto Detection
or
Other Inform

Worker Dispatch

Close the case

KPI system will calculate
the defect rate.

物聯網引言

1

1. 既有經驗
2. 物聯網常見技術

物聯網商機及成功案例

2

1. 智慧交通
2. 智慧防汎
3. 消防聯網
4. 地層下陷預防
5. 共享停車
6. 智慧城市-智慧路燈

ORing 產品介紹

3


1. 平台及硬體架構
2. 產品說明
3. 節電設計說明
4. 維運APP 及平台
5. Open Gateway

Why ORing?

4

1. 物聯網成功關鍵

IIoT Platform Architecture



物聯網產品



骨幹網路

P

管理平台

無線通訊

S

整體方案

T



LoRa , NB-IoT , CatM1 , Wifi, BLE



Air box, Meter, Parking, Waste, Water Quality



骨幹及機房網路

工業規格，高耐溫，保固五年

主要產品

工業級乙太網路交換機
工業級光電轉換器
工業級串列設備聯網伺服器
工業級無線網路基地台
工業級無線行動路由器
工業級網路配件及網路管理軟體

主要功能

資料採集
高速網路管理
網路備援系統設計
VPN 建立及管理
網路設備管理系統

應用

有線及大資料通訊
系統骨幹網路
機房網路建立



無線通訊

工業規格，高耐溫，保固五年

主要產品	NB-IoT Gateway LoRa Gateway NB-IoT Sensor Node LoRa Sensor Node
主要功能	RS-485 資料採集 內建Sensor 回報資料 內建電池設備，減少佈線成本 低功耗設備 通訊格式轉換
應用	環境感應器整合 PLC 控制器整合 管理平台界接

The diagram illustrates the connectivity of various sensor nodes to a central gateway. The gateway is shown with multiple communication interfaces: Modbus, Serial, and LoRa. It receives data from different types of sensors and actuators, such as a temperature sensor, a humidity sensor, a light sensor, and a motor driver. The gateway then connects to a cloud platform (MQTT, NB-IoT, CAT-M1) or a local network (4G LTE, Ethernet) through a LoRaWAN Gateway.



ORIO 內建電池型產品系列

除標準PSM, EDRX 的模組標準休眠模式外
搭配低功耗MCU，擬定動作劇本，做最優化的電量使用

- 5~10年電池壽命
- 雙無線通訊備援
- 動作腳本優化



LoRa NBLoT
瓦斯表

- 半年電池壽命
- 雙無線通訊備援
- 動作腳本優化



NBLoT BT
車位地鎖


- 充放電控制
- 電壓偵測，低電量
警示



太陽能警示燈

ODM節電劇本設計

- 離峰or 尖峰時間自動切換
- 省電or 即時模式切換
- 待停or 占用模式



劇本設計

啟動定義、建議由各家廠商完成耗電量測及預估後，定義率表 廠商及SGS測試		實驗結果	
48			
0			
31			
使用DC 直流供應器，確認廠商所提供的電池最低工作電壓。(可正常上傳資料) 須可進行120次放電週期，方為通過測試，但以達到最低電壓為測試截止條件			
pre test 及耗電量測			
測試方法	SGS 測試值	行為每月重複次數	累積行為時間
取3min 的平均值	0.05 mA	長時間	31天的小時數 744 hr 37.2000 mAh
離開休眠待機模式時，成功從平臺得到開關閥指令的週期及平均電量。(需紀錄示波器或data logger 數值)	50 mA	25 s	1488 F * H / 3600 10.3333 hr 516.6667 mAh
離開休眠待機模式時，讀表並上傳度數(需紀錄示波器或data logger 數值)	50 mA	4 s	0 F * H / 3600 0 hr 0.0000 mAh
單月耗電總和		553.8667 mAh	
預估十年耗電		66464.0000 mAh	

電力計算驗證


Gain 20%
Battery Life

Save 10%
Maintain Fee

Save 5%
Project Budget



智慧安裝一站服務 - 訊號Survey/施工紀錄APP/管理報表



智慧安裝一站服務



1. Plan



APP shows the installation plan includes area and device.

2. Scan



Scan QR/Bar code of controller.



3. Record




Record the GPS, Pole ID and pics. Upload the all information and records to CMS.

4. Report




CMS check information and output the installation report.



ORing Open Gateway

Protocol Converter: ORing Open Gateway

ORing PaaS, AWS, Azure, CHT, AT&T ...



Modbus RTU, Modbus ASCII, Modbus TCP, SNMP, ...

Public/Private Cloud	ORing-PaaS, AWS, Azure, CHT, AT&T , APPIoT , Impact...	
MQTT, CoAP, LWM2M ...		
Open Gateway	ORing Device + Open Gateway Module (Physical Device)	PC + Open Gateway Pro (Software Solution)
Serial, Modbus TCP, Modbus RDU, ASCII, SNMP...		
Switches, PLC, Sensors...		



物聯網引言

1

1. 既有經驗
2. 物聯網常見技術

物聯網商機及成功案例

2

1. 智慧交通
2. 智慧防汎
3. 消防聯網
4. 地層下陷預防
5. 共享停車
6. 智慧城市-智慧路燈

ORing 產品介紹

3


1. 平台及硬體架構
2. 產品說明
3. 節電設計說明
4. 維運APP 及平台
5. Open Gateway

Why ORing?

4

1. 物聯網成功關鍵

物聯網成功關鍵






A dense network of blue circular nodes connected by thin blue lines, forming a complex web-like structure against a dark blue background.

TSN Time-Sensitive Networking

www.ORingnet.com


Get Connected Anytime, Anywhere

Industrial Ethernet Is Now Bigger Than Fieldbuses Industrial



What Is TSN?

- ▶ TSN is all about Layer 2 of the OSI model and is an extension to IEEE 802.1 to make Ethernet More Robust and Reliable
- ▶ Features are targeted at industrial, automotive, and AVB
- ▶ TSN uses time to ensure predictable message delivery



Status of Related Standards

Standard	Title	Status	Publication Date
IEEE 802.1BA-2011	Audio Video Bridging (AVB) Systems	Current, amended by Cor1-2016 [11]	30 September 2011
IEEE 802.1AS-2020	Timing and Synchronization for Time-Sensitive Applications (gPTP)	Current [12][13]	30 January 2020
IEEE 802.1Qav-2009	Forwarding and Queuing Enhancements for Time-Sensitive Streams		5 January 2010
IEEE 802.1Qat-2010	Stream Reservation Protocol (SRP)		30 September 2010
IEEE 802.1aq-2012	Shortest Path Bridging (SPB)		29 March 2012
IEEE 802.1Qbp-2014	Equal Cost Multiple Paths (for Shortest Path Bridging)		27 March 2014
IEEE 802.1Qbv-2015	Enhancements for Scheduled Traffic	Incorporated into IEEE 802.1Q	18 March 2016
IEEE 802.1Qbu-2016	Frame Preemption		30 August 2016
IEEE 802.1Qca-2015	Path Control and Reservation		11 March 2016
IEEE 802.1Qch-2017	Cyclic Queuing and Forwarding		28 June 2017
IEEE 802.1Qci-2017	Per-Stream Filtering and Policing		28 September 2017
IEEE 802.1Q-2018	Bridges and Bridged Networks (<i>incorporates 802.1Qav/Qat/aq/Qbp/Qbv/Qbu/Qca/Qci/Qch and other amendments</i>)	Current [14]	6 July 2018
IEEE 802.1AB-2016	Station and Media Access Control Connectivity Discovery (Link Layer Discovery Protocol (LLDP))	Current [15]	11 March 2016
IEEE 802.1ABdh	Station and Media Access Control Connectivity Discovery - Support for Multiframe Protocol Data Units (LLDPv2)	Preparation [16]	5 September 2019
IEEE 802.1AX-2020	Link Aggregation	Current [17][18]	30 January 2020
IEEE 802.1CB-2017	Frame Replication and Elimination for Reliability	Current [19]	27 October 2017
IEEE 802.1CBdb	FRER Extended Stream Identification Functions	Draft 0.5 [20]	20 February 2020
IEEE 802.1CM-2018	Time-Sensitive Networking for Fronthaul	Current [21][22]	8 June 2018
IEEE 802.1CMde	Enhancements to Fronthaul Profiles to Support New Fronthaul Interface, Synchronization, and Syntonization Standards	Draft 1.1 [23]	11 February 2020
IEEE 802.1Qcc-2018	Stream Reservation Protocol (SRP) Enhancements and Performance Improvements	Current [24]	31 October 2018
IEEE 802.1Qcy-2019	Virtual Station Interface (VSI) Discovery and Configuration Protocol (VDP)	Current [25]	4 June 2018
IEEE 802.1Qcj	Automatic Attachment to Provider Backbone Bridging (PBB) services	Draft 1.2 [26]	12 December 2019
IEEE 802.1Qcr	Asynchronous Traffic Shaping	Draft 2.0 [27]	16 December 2020

TSN Components

Time sync:

Timing and Sync (802.1AS)
includes a profile of IEEE 1588

Synchronization

Reliability

Latency

Resource Mgmt

Bounded low latency:

Credit Based Shaper (802.1Qav)
Preemption (802.3br & 802.1Qbu)
Scheduled Traffic (802.1Qbv)
Cyclic Q-ing & Fwd (802.1Qch)
Async Shaping (P802.1Qcr)

Zero congestion loss

Ultra reliability:

Frame Repl & Elim (802.1CB)
Path Control (802.1Qca)
Per-Stream Filtering (802.1Qci)
Time sync (P802.1AS-Rev)

Dedicated resources & API


Stream Resv Prot (802.1Qat)
TSN configuration (P802.1Qcc)
YANG (P802.1Qcp, etc.)
Link-local Resv Prot (P802.1CS)

802.1CB Seamless Redundancy

- ▶ Purpose:
Provide lightweight redundancy for reliable delivery of traffic streams


How?

- ▶ Send two copies of a message along maximally disjoint path to ensure delivery
- ▶ Use of redundant paths minimize packet loss due to Link or device failures Congestion
- ▶ Discard duplicate frames upon reception




802.1Qbv Time Aware Shaper

- 802.1Qbv defines Time-Aware shaper for Ethernet switches




802.1Qbu Preemption

Time-critical frames can suspend the transmission of non-time-critical frames while one or more time-critical frames are transmitted



TSN Video



Oring TSN Switch



	ORing Gen 1 TSN product (AVB)	ORing Gen 2 TSN product	ORing Gen 3 TSN product
Switch Chipset	BCM5616X	BCM5357X(L2) / BCM5617X(L3) VSC7558	BCM5357X(L2) / BCM5617X(L3) VSC7558
IEEE 802.1AS	✓	✓	✓
IEEE 802.1Qav	✓	✓	✓
IEEE 802.1Qat	✓	✓	✓
IEEE 802.1Qbv		✓	✓
IEEE 802.1Qbu			✓
IEEE 802.1Qca			✓
IEEE 802.1CB		✓	✓
IEEE 802.1Qci			✓
IEEE 802.1Qch			✓

TSN switch

Next Gen Switch
Modular Rack-mount Switch

Planning

IGS-RX164GP+ Product Hardware Specification

- 112Gbps switching fabric
- Forwarding rate: 95.23Mpps
- 4GB DDR3 SDRAM and 2GB Flash Memory
- Total VLAN entry size: 4K
- Full L3 Managed switch
 - OSPF/ RIPv1/v2/VRRP
 - 1,000 multicast routes at L3 (IPv4) managed level
 - up 512unicast routes at L3 (IPv6) managed level

- 16 x Gigabit copper speed

Copper Port

- Support 4 x 1G/2.5G/10G SFP+
- SFP plug, LC type, MM/SS, BIDI

SFP Port



- Dual Power Input (12-48VDC)
- Dual image firmware

Mechanical and Environments


- Hardened Grade (-40~70c)
- IP 30

EtherNet/IP




Industrial Ethernet Protocols

- Traditional Industrial Protocol to Ethernet-Based Protocol
 - Increased Speed (e.g.. RS-232 9.6 kbit/s to Gigabit Ethernet Gbit/s)
 - Increased Distance (Cat5e/Cat6 cables or optical fiber)
 - Better Interoperability with devices



Market Shares - HMS



EtherNet/IP Introduction

- Organization: ODVA, Founded 1995, over 300 members
- Industrial automation applications
- Part of ODVA CIP (Common Industrial Protocol)
 - A unified communication architecture allows users to integrate I/O control, device configuration and data collection across networks.
- Industrial Ethernet Protocols
 - EtherNet/IP is the CIP on Ethernet, it uses TCP/IP to encapsulate CIP messages, which is compatible with IEEE 802.3 standard Ethernet.

ORing CIP Object

- ORing switches support the following objects for PLCs and SCADA systems to monitor:
 - Identity Object - Vendor ID, Device Type, Product Name...
 - Assembly Object - Data, size...
 - TCP/IP Interface Object - IP Address, Gateway Address, Domain Name...
 - Ethernet Link Object - Interface Speed , Unicast packets...
 - Port Object - Port Number, Port Name...
 - ORing Networking Object (Vendor Specific) - O-Ring Master/Slave, O-Ring Port1 Status...

Monitor EtherNet/IP

1. Create Device on EtherNet/IP based software (Rockwell Studio 5000)
2. Upload the EDS File to the software
3. Create the Implicit messaging or Explicit Messaging monitor
4. Monitor EtherNet/IP messaging

Name	Value
+ IGPS9084GP:O	(...)
- IGPS9084GP:I	(...)
IGPS9084GP:I.Data	(...)
IGPS9084GP:I.Data[0]	80
IGPS9084GP:I.Data[0].0	0
IGPS9084GP:I.Data[0].1	0
IGPS9084GP:I.Data[0].2	0
IGPS9084GP:I.Data[0].3	0
IGPS9084GP:I.Data[0].4	1
IGPS9084GP:I.Data[0].5	0
IGPS9084GP:I.Data[0].6	1
IGPS9084GP:I.Data[0].7	0
IGPS9084GP:I.Data[0].8	0
IGPS9084GP:I.Data[0].9	0

EtherNet/IP Products

- 9000 Series L3/L2 Ethernet Switch
 - Rack-mount (e.g. RGS-R9XXX)
 - Din-Rail (e.g. IGPS-9XXX)



IGPS-9084GP



EtherNet/IP®




RGS-PR9000

- ✓ Compatible with Rockwell PLC/SCADA(Studio 5000/RSlogix5000)




Profinet




Industrial Ethernet Protocols


- Traditional Industrial Protocol to Ethernet-Based Protocol
 - Increased Speed (e.g.. RS-232 9.6 kbit/s to Gigabit Ethernet Gbit/s)
 - Increased Distance (Cat5e/Cat6 cables or optical fiber)
 - Better Interoperability with devices



Market Shares - HMS



Profinet test procedure



ORing Profinet Object

- ORing switches support the following objects for monitor:



Device Alarm (Index 1)

Byte	Name	Access	Value	Description
0	Status Alarm	Read/Write	0	Do not send any alarms
			1	Send alarm if any status change
1	Power Alarm 1	Read/Write	0	Do not send power failed alarms
			1	Send alarm if power 1 fails
2	Power Alarm 2	Read/Write	0	Do not send power failed alarms
			1	Send alarm if power 2 fails

Device Status (Index 2)

Byte	Name	Access	Value	Description
0	Device Status	Read Only	0	Unavailable
			1	Available
			2	Device bootup fails
1	Fault Status	Read Only	0	Unavailable
			1	Available
			2	Device detect fault
2	Power 1 Status	Read Only	0	Unavailable
			1	Available
			2	Power 1 fails
3	Power 2 Status	Read Only	0	Unavailable
			1	Available
			2	Power 2 fails
4	Power 3 Status	Read Only	0	Unavailable
			1	Available
			2	Power 3 fails
5	Reserved			
6	Redundant Mode	Read Only	0	Unavailable
			1	RSTP
			2	O-Ring
			3	O-Chain
7	Ring Status	Read Only	0	Unavailable
			1	Healthy
			2	Break

Monitor status via Profinet



Profinet Products

- 9000 Series L3/L2 Ethernet Switch
 - Din-Rail /Rack mount (e.g. IPS-9XXX/ RGS-9XXX)




Product roadmap



Industrial Ethernet Switch Product Roadmap

Unmanaged Products:



Industrial Ethernet Switch Product Roadmap

L2+ Managed Products:



IGPS-9084GP-LA-24V

- 8+4 full Gigabit
- 12 to 57 VDC
- 120W PoE



IGPS-9084GP-BT

- 8 x Gigabit
- 2 x SFP port
- 240W BT PoE

Planning



IGPS-9822DGP+-BT

- 8 x Gigabit
- 4 x 2.5G/10G SFP port
- 240W BT PoE

Planning

Industrial Ethernet Switch Product Roadmap

L2+/L3 Managed Products:



IGS-RX164GP+
-16+4 L3 switch
-10G SFP



IGPS-RX884GTP+
-8+8+4 L3 switch
-100W PoE budget



IGS-RX884DGP+
-8+8+4 L3 switch
-2.5G/10G SFP



RGS-X244DGP
-24+4 full Gigabit
-Cost effective



RG(P)S-PRX004GP+MG
-L3 switch
-3 slot for modular



Appendix – BT Measurement


4. Measurement Setup and Result

The PSE output power and delivered PD input power is measured. PSE output power which means the power transmitted onto Ethernet cable by PSE side. Delivered PD input power which means the power delivered at RJ-45 jack on PD device, notice that this power value will affect by cable loss. The simplified block diagram, setup picture and measured result are shown below.

Setup picture:



PSE output power measurement using short cable (left) and long cable (right).



Delivered PD input power measurement using short cable (left) and long cable (right).

PSE output power	Delivered PD input Power	
	Cable Length = 1M	Cable Length = 100M
45W	45W	41.3W
60W	60W	56W
75W	75W	66.7W
90W	90W	80.5W

*The length unit of the cable is meter.

*Ethernet Cable: TE connectivity CAT 5E 4UTP 24AWG.

Thank You.

